
Date: 14.01.2016 10:21:41
ECU: N62_TUE
JobStatus: OKAY
Variant: N62_TUE

RESULT: 3 error in error memory !

2A8B CDKENWSAD2 - intake-VANOS, Adaption limit stop 2

Error counter: 8
Logistic counter: 40

| | | |
|---------------------|--------|--------|
| 1. Umweltsatz | | |
| Mileage | 249952 | km |
| Engine speed | 760.00 | 1/min |
| relative air charge | 43.50 | % |
| Engine temperature | 21.00 | Grad C |
| Operation mode byte | 2.00 | - |

| | | |
|---------------------|--------|--------|
| 2. Umweltsatz | | |
| Mileage | 249952 | km |
| Engine speed | 880.00 | 1/min |
| relative air charge | 35.25 | % |
| Engine temperature | 35.25 | Grad C |
| Operation mode byte | 8.00 | - |

| | | |
|---------------------|--------|--------|
| 3. Umweltsatz | | |
| Mileage | 249984 | km |
| Engine speed | 720.00 | 1/min |
| relative air charge | 27.00 | % |
| Engine temperature | 96.75 | Grad C |
| Operation mode byte | 8.00 | - |

Limit stop adaptionen out of valid range
Test conditions fulfilled
Error present now and already stored
Error would not cause a warning lamp to light up
Diagnostic active
Cycle flag set
Failure within debounce phase

Error code: 2A 8B 62 25 00 00 08 28 7A 0C 13 3A 5C 02 7A 0C
16 2F 6F 08 7A 10 12 24 C1 08

2A8C CDKANWSAD - outlet-VANOS, Adaption limit stop

Error counter: 1
Logistic counter: 40

| | | |
|---------------------|--------|--------|
| Mileage | 249952 | km |
| Engine speed | 760.00 | 1/min |
| relative air charge | 43.50 | % |
| Engine temperature | 21.00 | Grad C |
| Operation mode byte | 2.00 | - |

camshaft adjustment has not reached late position
Test conditions fulfilled
Error present now and already stored
Error would not cause a warning lamp to light up
Diagnostic active
Cycle flag set
Failure within debounce phase

Error code: 2A 8C 62 25 00 00 01 28 7A 0C 13 3A 5C 02 00 00
00 00 00 00 00 00 00 00 00 00

2A8A CDKENWSAD - intake-VANOS, Adaption limit stop

Error counter: 6
Logistic counter: 40

1. Umweltsatz

| | | |
|---------------------|--------|--------|
| Mileage | 249952 | km |
| Engine speed | 720.00 | 1/min |
| relative air charge | 48.00 | % |
| Engine temperature | 22.50 | Grad C |
| Operation mode byte | 8.00 | - |

2. Umweltsatz

| | | |
|---------------------|--------|--------|
| Mileage | 249952 | km |
| Engine speed | 840.00 | 1/min |
| relative air charge | 33.00 | % |
| Engine temperature | 36.75 | Grad C |
| Operation mode byte | 8.00 | - |

3. Umweltsatz

| | | |
|---------------------|--------|--------|
| Mileage | 249992 | km |
| Engine speed | 880.00 | 1/min |
| relative air charge | 36.75 | % |
| Engine temperature | 33.00 | Grad C |
| Operation mode byte | 8.00 | - |

Limit stop adaptionen out of valid range
Test conditions fulfilled
Error present now and already stored
Error would not cause a warning lamp to light up
Diagnostic active
Cycle flag set

Error code: 2A 8A 62 05 00 00 06 28 7A 0C 12 40 5E 08 7A 0C
15 2C 71 08 7A 11 16 31 6C 08

=====